

## LED SMD Floodlight Black City Line

Power

20W

Light color

Luce fredda



### Technical Specification

|   |                  |                           |               |
|---|------------------|---------------------------|---------------|
| <b>Beam angle</b>                               | 120°             | <b>Power</b>              | 20W           |
| <b>Brand</b>                                    | Optonica         | <b>On/Off Cycles</b>      | 100 000x      |
| <b>Color Code</b>                               | 860              | <b>FLUX per watt</b>      | 80 lm/W       |
| <b>Color Designation</b>                        | White Light (WH) | <b>Flux</b>               | 1600 lm       |
| <b>Correlated Color Temperature</b>             | 6000K            | <b>Life span</b>          | 25000h        |
| <b>Items per box</b>                            | 40               | <b>Wattage Equivalent</b> | 107W          |
| <b>Items per pack</b>                           | 1                | <b>Material</b>           | Aluminium     |
| <b>Lumen maintenance at end of service life</b> | 70%              | <b>Instant On</b>         | 0.1 s         |
| <b>Operating Frequency</b>                      | 50-60Hz          | <b>Product Code</b>       | FL20-B1       |
| <b>Ra ≥</b>                                     | 80               | <b>Size of product</b>    | 142x130x24 mm |
| <b>Warranty</b>                                 | 2 Years          | <b>Temperature</b>        | -20°C/ +50°C  |
| <b>Energy Efficiency Label</b>                  | F                | <b>EAN Code</b>           | 3800156659186 |
| <b>Input voltage</b>                            | AC220-265V       | <b>Size of package</b>    | 148X30X135 mm |
| <b>IP</b>                                       | 65               | <b>Weight of Product</b>  | 303 gr.       |
| <b>Energy Consumption</b>                       | 20 kWh/1000h     | <b>Light Color</b>        | Luce fredda   |