

# OPTONICA

## DATASHEET



### LED Linear Suspended Light Linkable 5 Years Warranty

Power

40W

Light color

Neutralweiß

## Technical Specification

|                                          |                    |                    |                 |
|------------------------------------------|--------------------|--------------------|-----------------|
| Beam angle                               | 120°               | Body Color         | Black           |
| Brand                                    | Optonica           | Flux               | 4000 lm         |
| Dimmable                                 | No                 | Color Of The Shell | Black           |
| Items per pack                           | 1                  | Input voltage      | AC200-240V      |
| Lumen maintenance at end of service life | 70%                | Life span          | 25000h          |
| On/Off Cycles                            | 25 000x            | Size of package    | 1430x80x45 mm   |
| Operating Frequency                      | 50-60Hz            | Weight of Product  | 1.830 kg        |
| Ra ≥                                     | 80                 | Material           | Aluminium       |
| Color Code                               | 840                | Instant On         | 0.1 s           |
| Correlated Color Temperature             | 4000K              | Temperature        | -20°C/ +40°C    |
| Warranty                                 | 5 Years            | IP                 | IP20            |
| Color Designation                        | Neutral White (NW) | Product Code       | LN40-A3         |
| Energy Efficiency Label                  | E                  | EAN Code           | 3800156653801   |
| FLUX per watt                            | 100lm/W            | Size of Box        | 1330x250x185 mm |
| Energy Consumption                       | 40 kWh/1000h       | Size of product    | 1185x50x70 mm   |
| Power                                    | 40W                | Light Color        | Neutralweiß     |
| Items per box                            | 6                  |                    |                 |