

# OPTONICA

## DATASHEET



### T-Shape Connector White

Power

12W

Light color



Lumière  
neutre

## Technical Specification

|                                          |                    |                    |                   |
|------------------------------------------|--------------------|--------------------|-------------------|
| Beam angle                               | 120°               | Power              | 12W               |
| Brand                                    | Optonica           | FLUX per watt      | 85 lm/W           |
| Dimmable                                 | No                 | Items per box      | 5                 |
| IP                                       | 20                 | On/Off Cycles      | 100 000x          |
| Items per pack                           | 1                  | Body Color         | White             |
| Life span                                | 25 000 Hours       | Input voltage      | AC200-240V        |
| Lumen maintenance at end of service life | 70%                | Color Of The Shell | White             |
| Operating Frequency                      | 50-60Hz            | Material           | Aluminium         |
| Warranty                                 | 2 Years            | Temperature        | -20°C / +50°C     |
| Color Code                               | 840                | Others             | For use with 5377 |
| Correlated Color Temperature             | 4000K              | Product Code       | OT12-A1           |
| Energy Efficiency Label                  | F                  | Size of product    | 255x127x35 mm     |
| Instant On                               | 0.1s               | Weight of Product  | 965 gr.           |
| Power Factor                             | 0.5                | EAN Code           | 3800156650343     |
| Color Designation                        | Neutral White (NW) | Flux               | 1020 lm           |
| Energy Consumption                       | 12 kWh/1000h       | Light Color        | Lumière neutre    |