

### LED Super Slim Build-In+Surface Panel CCT



Power

30W

Light color

Cambio colore  
3000K -  
6000K

## Technical Specification

|   |                   |                                     |                             |
|---|-------------------|-------------------------------------|-----------------------------|
| <b>Brand</b>                                    | Optonica          | <b>Energy Consumption</b>           | 30 kWh/1000h                |
| <b>Dimmable</b>                                 | No                | <b>Power</b>                        | 30W                         |
| <b>IP</b>                                       | 20                | <b>Body Color</b>                   | White                       |
| <b>Items per pack</b>                           | 1                 | <b>Color Of The Shell</b>           | White                       |
| <b>Life span</b>                                | 25 000 Hours      | <b>Color Change Mode</b>            | CCT                         |
| <b>Lumen maintenance at end of service life</b> | 70%               | <b>Correlated Color Temperature</b> | 3000K-6000K                 |
| <b>On/Off Cycles</b>                            | 25 000x           | <b>Flux</b>                         | 3000 lm                     |
| <b>Operating Frequency</b>                      | 50-60Hz           | <b>Color Code</b>                   | 830-860                     |
| <b>Ra ≥</b>                                     | 80                | <b>Color Designation</b>            | CCT                         |
| <b>Temperature</b>                              | -30°C / +50°C     | <b>Input voltage</b>                | AC:175-265V                 |
| <b>Warranty</b>                                 | 2 Years           | <b>Mount Type</b>                   | Recessed/Surface            |
| <b>Instant On</b>                               | 0.1s              | <b>EAN Code</b>                     | 3800156625877               |
| <b>Material</b>                                 | Plastic+Aluminium | <b>Product Code</b>                 | DL30-A7                     |
| <b>Energy Efficiency Label</b>                  | E                 | <b>Size of package</b>              | 340x340x35 mm               |
| <b>FLUX per watt</b>                            | 100lm/W           | <b>Size of product</b>              | φ330x19 mm                  |
| <b>Power Factor</b>                             | 0.9               | <b>Weight of Product</b>            | 934 gr.                     |
| <b>Wattage Equivalent</b>                       | 200W              | <b>Hole Size</b>                    | φ65-310 mm                  |
| <b>Items per box</b>                            | 10                | <b>Light Color</b>                  | Cambio colore 3000K - 6000K |
| <b>Beam angle</b>                               | 100°              |                                     |                             |