

## LED Strip 2216 High Power 24V IP20

Power

22W/m

Light color



Luce calda

### Technical Specification

|   |                 |                           |                 |
|---|-----------------|---------------------------|-----------------|
| <b>Beam angle</b>                               | 120°            | <b>Warranty</b>           | 3 Years         |
| <b>Brand</b>                                    | Optonica        | <b>Material</b>           | Flex PCB        |
| <b>IP</b>                                       | 20              | <b>Roll</b>               | 5m              |
| <b>Life span</b>                                | 25 000 Hours    | <b>Ra ≥</b>               | 90              |
| <b>Lumen maintenance at end of service life</b> | 70%             | <b>Size of product</b>    | 10x2 mm         |
| <b>Operating Frequency</b>                      | 50-60Hz         | <b>EAN Code</b>           | 3800156644038   |
| <b>Temperature</b>                              | -30°C / +50°C   | <b>Energy Consumption</b> | 22 kWh/m/ 1000h |
| <b>Color Code</b>                               | 830             | <b>Flux</b>               | 1900lm          |
| <b>Correlated Color Temperature</b>             | 3000K           | <b>Input voltage</b>      | DC24V           |
| <b>Energy Efficiency Label</b>                  | F               | <b>LEDs/m</b>             | 240             |
| <b>Instant On</b>                               | 0.1s            | <b>Power</b>              | 22W/m           |
| <b>Color Designation</b>                        | Warm White (WW) | <b>Power per meter</b>    | 22W             |
| <b>Dimmable</b>                                 | Yes             | <b>Product Code</b>       | ST2216-A1       |
| <b>LED Type</b>                                 | SMD             | <b>Weight of Product</b>  | 97gr. /roll     |
| <b>Power Factor</b>                             | 0.9             | <b>Light Color</b>        | Luce calda      |
| <b>On/Off Cycles</b>                            | 100 000x        |                           |                 |